

INDICADOR DE DESGASTE DE DISCO DE FRENO- CARBOTEQ



SKU: N / A | **Categorías:** [Ensayos no destructivos](#), [Propiedades de metales y cerámica de carbono](#) | **Etiquetas:** [Proceq](#)

DESCRIPCIÓN DEL PRODUCTO

[vc_row type="full_width_background" full_screen_row_position="middle" scene_position="center" text_color="dark" text_align="left" top_padding="60" overlay_strength="0.3"][vc_column column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1" column_shadow="none" width="1/1" tablet_text_alignment="default" phone_text_alignment="default" column_border_width="none" column_border_style="solid"][vc_column_text]

Indicación ultraprecisa del desgaste de discos de freno cerámicos de carbono

Usando nuestra experiencia y colaborando estrechamente con BSCCB (Brembo SGL Carbon Ceramic Brakes), Proceq estuvo en condiciones de desarrollar Carboteq, un instrumento único y patentado para medir en forma precisa el desgaste de discos de freno.

Carboteq se basa en la tecnología de inducción de impulsos usando una disposición específica de bobinas inductivas y un avanzado análisis de las señales para compensar las influencias de las características del material y de las geometrías de los discos de freno

[vc_column_text][vc_column][vc_row][vc_row type="full_width_background" full_screen_row_position="middle" scene_position="center" text_color="dark" text_align="left" overlay_strength="0.3"][vc_column column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1" column_shadow="none" width="1/2" tablet_text_alignment="default" phone_text_alignment="default" column_border_width="none" column_border_style="solid"][image_with_animation image_url="16522" alignment="center" animation="Fade In" box_shadow="none" max_width="100%"][vc_column][vc_column column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1" top_margin="40" column_shadow="none" width="1/2" tablet_text_alignment="default" phone_text_alignment="default" column_border_width="none" column_border_style="solid"][vc_column_text]

Descripción general

[vc_column_text][vc_row_inner column_margin="default" text_align="left"][vc_column_inner column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" width="1/2" column_border_width="none" column_border_style="solid"][vc_column_text]Sus ventajas[vc_column_text][vc_column_inner][vc_column_inner column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" el_class="general" width="1/2" column_border_width="none" column_border_style="solid"][vc_column_text]

- Carboteq obtiene mejores resultados que cualquier otro método de medición existente
- Ninguna necesidad de desmantelar la unidad en el extremo de la rueda
- Sólo tres pasos hasta el resultado de la prueba

[vc_column_text][vc_column_inner][vc_row_inner][vc_row_inner column_margin="default" text_align="left"][vc_column_inner column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" width="1/2" column_border_width="none" column_border_style="solid"][vc_column_text]Escala nativa[vc_column_text][vc_column_inner][vc_column_inner column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" el_class="general" width="1/2" column_border_width="none" column_border_style="solid"][vc_column_text]

- CQ

[vc_column_text][vc_column_inner][vc_row_inner][vc_row_inner column_margin="default" text_align="left"][vc_column_inner column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" width="1/2" column_border_width="none" column_border_style="solid"][vc_column_text]Rango de medición[vc_column_text][vc_column_inner][vc_column_inner column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" el_class="general"

```
width="1/2" column_border_width="none" column_border_style="solid"]vc_column_text]De 0,0 a 100,0
CQ[/vc_column_text]/[vc_column_inner]/[vc_row_inner]/[vc_row_inner column_margin="default"
text_align="left"]vc_column_inner column_padding="no-extra-padding" column_padding_position="all"
background_color_opacity="1" width="1/2" column_border_width="none"
column_border_style="solid"]vc_column_text]Incertidumbre
expandida[/vc_column_text]/[vc_column_inner]/[vc_column_inner column_padding="no-extra-padding"
column_padding_position="all" background_color_opacity="1" el_class="general" width="1/2"
column_border_width="none" column_border_style="solid"]vc_column_text]
```

- De 0 a 40 °C: $U = 2,0 \text{ CQ}$ ($k = 2$)
- De -10 a 60 °C: $U = 3,0 \text{ CQ}$ ($k = 2$)

```
[/vc_column_text]/[vc_column_inner]/[vc_row_inner]/[vc_column]/[vc_row]/[vc_row type="full_width_background"
full_screen_row_position="middle" scene_position="center" text_color="dark" text_align="left"
overlay_strength="0.3"]vc_column column_padding="no-extra-padding" column_padding_position="all"
background_color_opacity="1" background_hover_color_opacity="1" top_margin="40" column_shadow="none" width="1/2"
tablet_text_alignment="default" phone_text_alignment="default" column_border_width="none"
column_border_style="solid"]vc_column_text]
```

Aplicaciones

- Indicación de desgaste de discos CCB
- Indicación de desgaste de discos CCM

```
[/vc_column_text]/[vc_column]/[vc_column column_padding="no-extra-padding" column_padding_position="all"
background_color_opacity="1" background_hover_color_opacity="1" column_shadow="none" width="1/2"
tablet_text_alignment="default" phone_text_alignment="default" column_border_width="none"
column_border_style="solid"]image_with_animation image_url="16523" alignment="center" animation="Fade In"
box_shadow="none" max_width="100%"]vc_column]/[vc_row]/[vc_row type="full_width_background"
full_screen_row_position="middle" scene_position="center" text_color="dark" text_align="left"
overlay_strength="0.3"]vc_column column_padding="no-extra-padding" column_padding_position="all"
background_color_opacity="1" background_hover_color_opacity="1" column_shadow="none" width="1/2"
tablet_text_alignment="default" phone_text_alignment="default" column_border_width="none"
column_border_style="solid"]image_with_animation image_url="5153" alignment="center" animation="Fade In"
box_shadow="none" max_width="100%"]vc_column]/[vc_column column_padding="no-extra-padding"
column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1"
column_shadow="none" width="1/2" tablet_text_alignment="default" phone_text_alignment="default"
column_border_width="none" column_border_style="solid"]vc_column_text]
```

Características

```
[/vc_column_text]/[vc_row_inner column_margin="default" text_align="left"]vc_column_inner column_padding="no-extra-
padding" column_padding_position="all" background_color_opacity="1" width="1/2" column_border_width="none"
column_border_style="solid"]vc_column_text]Idiomas[/vc_column_text]/[vc_column_inner]/[vc_column_inner
column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" width="1/2"
column_border_width="none" column_border_style="solid"]vc_column_text]
```

- Instrumento: independiente del idioma
- Documentación: 21 idiomas están cubiertos

```
[/vc_column_text]/[vc_column_inner]/[vc_row_inner]/[vc_row_inner column_margin="default"
text_align="left"]vc_column_inner column_padding="no-extra-padding" column_padding_position="all"
background_color_opacity="1" width="1/2" column_border_width="none"
```

column_border_style="solid"][vc_column_text]Interfaz[/vc_column_text][vc_column_inner][vc_column_inner
column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" width="1/2"
column_border_width="none"
column_border_style="solid"][vc_column_text]USB[/vc_column_text][vc_column_inner][vc_row_inner][vc_row_inner
column_margin="default" text_align="left"][vc_column_inner column_padding="no-extra-padding"
column_padding_position="all" background_color_opacity="1" width="1/2" column_border_width="none"
column_border_style="solid"][vc_column_text]Láser[/vc_column_text][vc_column_inner][vc_column_inner
column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" width="1/2"
column_border_width="none" column_border_style="solid"][vc_column_text]Clase 2, < 1 mW, 650
nm[/vc_column_text][vc_column_inner][vc_row_inner][vc_row_inner column_margin="default"
text_align="left"][vc_column_inner column_padding="no-extra-padding" column_padding_position="all"
background_color_opacity="1" width="1/2" column_border_width="none"
column_border_style="solid"][vc_column_text]Batería[/vc_column_text][vc_column_inner][vc_column_inner
column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" width="1/2"
column_border_width="none" column_border_style="solid"][vc_column_text]

- 3,7 V / 380 mAh
- Recargable vía USB (5 VDC/100 mA)

[/vc_column_text][/vc_column_inner][/vc_row_inner][/vc_column][/vc_row]

INFORMACIÓN ADICIONAL

COTECNO