

TRANSMISOR DE VIENTO PARA FLUJO DE AIRE



SKU: N / A | **Categorías:** [Thies Clima](#), [Viento](#) |

DESCRIPCIÓN DEL PRODUCTO

```
[vc_row type="in_container" full_screen_row_position="middle" column_margin="default" scene_position="center" text_color="dark" text_align="left" overlay_strength="0.3" shape_divider_position="bottom" bg_image_animation="none"][vc_column column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1" column_link_target="_self" column_shadow="none" column_border_radius="none" width="1/1" tablet_width_inherit="default" tablet_text_alignment="default" phone_text_alignment="default" overlay_strength="0.3" column_border_width="none" column_border_style="solid" bg_image_animation="none"][vc_column_text]Transmisores de viento para flujo de aire direccional
```

Las aplicaciones típicas son:

- Ejes de ventilación
- Conductos de aire acondicionado
- Túneles de carretera y ferrocarril

```
[/vc_column_text][vc_row_inner column_margin="default" text_align="left" css=".vc_custom_1597668708409{border-radius: 2px !important;}"][vc_column_inner column_padding="no-extra-padding" column_padding_position="all" background_color="#9492ff" background_color_opacity="1" background_hover_color_opacity="1" font_color="ffffff" column_shadow="none" column_border_radius="none" column_link_target="_self" width="1/4" tablet_width_inherit="default" overlay_strength="0.3" column_border_width="none" column_border_style="solid" bg_image_animation="none"][vc_column_text]
```

Imagen

```
[/vc_column_text][vc_column_inner][vc_column_inner column_padding="no-extra-padding" column_padding_position="all" background_color="#9492ff" background_color_opacity="1" background_hover_color_opacity="1" font_color="ffffff" column_shadow="none" column_border_radius="none" column_link_target="_self" width="1/4" tablet_width_inherit="default" overlay_strength="0.3" column_border_width="none" column_border_style="solid" bg_image_animation="none"][vc_column_text]
```

Nombre del Producto

```
[/vc_column_text][vc_column_inner][vc_column_inner column_padding="no-extra-padding" column_padding_position="all" background_color="#9492ff" background_color_opacity="1" background_hover_color_opacity="1" font_color="ffffff" column_shadow="none" column_border_radius="none" column_link_target="_self" width="1/2" tablet_width_inherit="default" overlay_strength="0.3" column_border_width="none" column_border_style="solid" bg_image_animation="none"][vc_column_text]
```

Descripción corta

```
[/vc_column_text][vc_column_inner][vc_row_inner][vc_row_inner column_margin="default" text_align="left"][vc_column_inner column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1" column_shadow="none" column_border_radius="none" column_link_target="_self" width="1/4" tablet_width_inherit="default" overlay_strength="0.3" column_border_width="none" column_border_style="solid" bg_image_animation="none"][image_with_animation image_url="138460" alignment="center" animation="Fade In" hover_animation="none" border_radius="none" box_shadow="none" image_loading="default" max_width="100%" max_width_mobile="default"][/vc_column_inner][vc_column_inner column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1" column_shadow="none" column_border_radius="none" column_link_target="_self" width="1/4" tablet_width_inherit="default" overlay_strength="0.3" column_border_width="none" column_border_style="solid"
```

bg_image_animation="none"]][vc_column_text]

Transmisor de viento para aplicación en túneles

4.3308.10.000[/vc_column_text][vc_column_inner][vc_column_inner column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1" column_shadow="none" column_border_radius="none" column_link_target="_self" width="1/2" tablet_width_inherit="default" overlay_strength="0.3" column_border_width="none" column_border_style="solid" bg_image_animation="none"]][vc_column_text]Para la medición de flujos de aire direccionales, especialmente en túneles. El instrumento envía señales de frecuencia, dependiendo de la velocidad y relacionadas con la dirección del flujo.[vc_column_text][nectar_cta btn_style="see-through" heading_tag="h6" button_color="default" link_type="new_tab" alignment="left" display="block" link_text="Leer más" url="http://test.cotecno.cl/nuestros-productos/transmisor-de-viento-para-aplicacion-en-tuneles/"]][vc_column_inner][vc_row_inner]

[vc_row_inner column_margin="default" text_align="left"]][vc_column_inner column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1" column_shadow="none" column_border_radius="none" column_link_target="_self" width="1/4" tablet_width_inherit="default" overlay_strength="0.3" column_border_width="none" column_border_style="solid" bg_image_animation="none"]][image_with_animation image_url="138462" alignment="center" animation="Fade In" hover_animation="none" border_radius="none" box_shadow="none" image_loading="default" max_width="100%" max_width_mobile="default"]][vc_column_inner][vc_column_inner column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1" column_shadow="none" column_border_radius="none" column_link_target="_self" width="1/4" tablet_width_inherit="default" overlay_strength="0.3" column_border_width="none" column_border_style="solid" bg_image_animation="none"]][vc_column_text]

Anemómetro ultrasónico 1D

4.3865.0x.xxx[/vc_column_text][vc_column_inner][vc_column_inner column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1" column_shadow="none" column_border_radius="none" column_link_target="_self" width="1/2" tablet_width_inherit="default" overlay_strength="0.3" column_border_width="none" column_border_style="solid" bg_image_animation="none"]][vc_column_text]El anemómetro ultrasónico 1D sirve para medir el flujo de aire horizontal de una dirección de flujo fija y la temperatura acústico-virtual.

El dispositivo tiene un cable fijo de 5 m

Componentes calefactados:

- Brazos sensores

[vc_column_text][nectar_cta btn_style="see-through" heading_tag="h6" button_color="default" link_type="new_tab" alignment="left" display="block" link_text="Leer más" url="http://test.cotecno.cl/nuestros-productos/anemometro-ultrasonico-1d/"]][vc_column_inner][vc_row_inner]

[vc_row_inner column_margin="default" text_align="left"]][vc_column_inner column_padding="no-extra-padding" column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1" column_shadow="none" column_border_radius="none" column_link_target="_self" width="1/4" tablet_width_inherit="default" overlay_strength="0.3" column_border_width="none" column_border_style="solid"

```
bg_image_animation="none"][image_with_animation image_url="138462" alignment="center" animation="Fade In"
hover_animation="none" border_radius="none" box_shadow="none" image_loading="default" max_width="100%"
max_width_mobile="default"][/vc_column_inner][vc_column_inner column_padding="no-extra-padding"
column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1"
column_shadow="none" column_border_radius="none" column_link_target="_self" width="1/4"
tablet_width_inherit="default" overlay_strength="0.3" column_border_width="none" column_border_style="solid"
bg_image_animation="none"][/vc_column_text]
```

Anemómetro ultrasónico 1D

```
4.3866.0x.xxx[/vc_column_text][vc_column_inner][vc_column_inner column_padding="no-extra-padding"
column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1"
column_shadow="none" column_border_radius="none" column_link_target="_self" width="1/2"
tablet_width_inherit="default" overlay_strength="0.3" column_border_width="none" column_border_style="solid"
bg_image_animation="none"][/vc_column_text]El anemómetro ultrasónico 1D sirve para medir el flujo
de aire horizontal de una dirección de flujo fija y la temperatura acústico-virtual.
```

El dispositivo tiene un 8 pol. conector enchufable

Componentes calefactados:

- Brazos sensores

```
[/vc_column_text][nectar_cta btn_style="see-through" heading_tag="h6" button_color="default" link_type="new_tab"
alignment="left" display="block" link_text="Leer más"
url="http://test.cotecno.cl/nuestros-productos/anemometro-ultrasonico-1d-2/"][/vc_column_inner][vc_row_inner]
```

```
[vc_row_inner column_margin="default" text_align="left"][/vc_column_inner column_padding="no-extra-padding"
column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1"
column_shadow="none" column_border_radius="none" column_link_target="_self" width="1/4"
tablet_width_inherit="default" overlay_strength="0.3" column_border_width="none" column_border_style="solid"
bg_image_animation="none"][image_with_animation image_url="138462" alignment="center" animation="Fade In"
hover_animation="none" border_radius="none" box_shadow="none" image_loading="default" max_width="100%"
max_width_mobile="default"][/vc_column_inner][vc_column_inner column_padding="no-extra-padding"
column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1"
column_shadow="none" column_border_radius="none" column_link_target="_self" width="1/4"
tablet_width_inherit="default" overlay_strength="0.3" column_border_width="none" column_border_style="solid"
bg_image_animation="none"][/vc_column_text]
```

Anemómetro ultrasónico 1D

```
4.3867.0x.xxx[/vc_column_text][vc_column_inner][vc_column_inner column_padding="no-extra-padding"
column_padding_position="all" background_color_opacity="1" background_hover_color_opacity="1"
column_shadow="none" column_border_radius="none" column_link_target="_self" width="1/2"
tablet_width_inherit="default" overlay_strength="0.3" column_border_width="none" column_border_style="solid"
bg_image_animation="none"][/vc_column_text]El anemómetro ultrasónico 1D sirve para medir el flujo
de aire horizontal de una dirección de flujo fija y la temperatura acústico-virtual.
```

El dispositivo tiene un 8 pol. conector de enchufe y está montado en un mástil.

Componentes calefactados:

- Brazos sensores

[/vc_column_text][nectar_cta btn_style="see-through" heading_tag="h6" button_color="default" link_type="new_tab" alignment="left" display="block" link_text="Leer más" url="http://test.cotecno.cl/nuestros-productos/anemometro-ultrasonico-1d-3/"][/vc_column_inner][/vc_row_inner]

[/vc_column][/vc_row]

COTECNO

INFORMACIÓN ADICIONAL

COTECNO